

Automotive Chemicals – Technical Spray - Assembly

Version: **TS/031**

Valvoline™ Ceramic Grease

High quality metal-free ceramic grease, to treat parts which are subjected to heavy workloads and/ or exposed to very high temperatures.

Applications

ABS brake systems
Lambda sensors
Brake parts
Exhaust parts
Screwed connections, which are exposed to high temperatures
Industrial ovens

Product characteristics

Protects against electrolytic corrosion
High thermal stability
Resistant to chemicals and weather influences
Resistant to water, salt and weak acids and bases
Prevents wear and sticking
Extremely suitable to mount ABS break systems and lambda sensors
Directed jet spray
Simplifies the future removal

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Ceramic Grease should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Apply Valvoline™ Ceramic Grease.

The specific lubrication properties of Valvoline™ Ceramic Grease will be obtained after evaporation of the solvent (approx. 1 minute).

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Ceramic Grease	
Contents	500 ml
Basis	Very fine ceramic particles
VOC-content	Approx. 68% w/w
Colour	White
Scent	Characteristic
Appearance	Pasty
Relative density at 20°C	1,26 g/ml
Yield	1,65 g/sec
Vapor pressure at 20°C	3 to 4 bar
Temperature resistant	-40°C to +1200°C

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –