**HYDRAULIC FLUID** 





## **PENTOSIN CHF 11S**

## **Long-Life Synthetic Hydraulic Fluid For Modern Vehicles**

## **DESCRIPTION**

Pentosin CHF 11S is a synthetic high performance hydraulic fluid for lifetime application in modern vehicle aggregates. Pentosin CHF 11S is especially designed for hydraulics in the automotive industry with the highest technical requirements such as in: power steering, level control, shock absorber, hydro-pneumatic suspension, stability and traction control, hydraulics for convertible tops, central lock systems, etc. It is suitable for all extreme conditions and guarantees full performance from -40°C to over 130°C system temperature.

| PRODUCT AT                   | TRIBUTES    |                         |
|------------------------------|-------------|-------------------------|
| Appearance                   |             | Dark Green              |
| Density at 20°C              |             | 825 kg/m³               |
| Kinematic Viscosity at 100°C |             | 6.0 mm <sup>2</sup> /s  |
| Kinematic Viscosity at 40°C  |             | 18.7 mm <sup>2</sup> /s |
| Kinematic Viscosity at -40°C |             | 1100 mm <sup>2</sup> /s |
| Viscosity Index              |             | 313                     |
| Pour Point                   |             | -57°C/-70.6°F           |
| Flash Point                  |             | 160°C/320°F             |
| Ignition Temperature         |             | 235°C/455°F             |
| SIZE                         | PART NUMBER | GTIN-13                 |
| 1 Liter                      | 1405116     | 4008849503016           |
| 5 Liter                      | 1405216     | 4008849512346           |
| 20 Liter                     | 1405208     | 4008849522345           |
|                              |             |                         |

| OE REFERENCE NUMBERS/RECOMMENDATIONS |                  |  |
|--------------------------------------|------------------|--|
| Make                                 | Reference Number |  |
| Audi/Volkswagen                      | G 002 000 A2     |  |
| Bentley                              | RH 5000          |  |
| BMW/MINI                             | 82 11 0 148 132  |  |
| BMW/MINI                             | 82 11 1 468 041  |  |
| BMW/MINI                             | 83 29 0 429 576  |  |
| Chrysler/Dodge/Jeep                  | 05127381AB       |  |
| Chrysler/Dodge/Jeep                  | 68088485AA       |  |
| Fendt                                | X 902 011 622    |  |
| Mercedes-Benz                        | 001 989 24 03 10 |  |
| Mercedes-Benz                        | 001 989 24 03 12 |  |
| Mercedes-Benz                        | Q 1 32 0001      |  |
| Porsche                              | 000 043 203 33   |  |
| Saab                                 | 3032 380         |  |
| Volvo                                | 11 61 529        |  |

| APPROVALS/SPECIFICATIONS |                   |  |
|--------------------------|-------------------|--|
| Organization Name        | Specification Met |  |
| Audi/Volkswagen          | TL 52 146.00      |  |
| Bentley                  | Bentley approved  |  |
| BMW                      | BMW approved      |  |
| Chrysler                 | MS-11655          |  |
| DIN                      | 51 524 T3         |  |
| Dodge                    | MS-11655          |  |
| Fendt                    | Fendt approved    |  |
| Ford                     | Ford WSS-M2C204-A |  |
| GM/Opel                  | GM/Opel approved  |  |
| ISO                      | 7308              |  |
| Jeep                     | MS-11655          |  |
| MAN                      | M 3289            |  |
| MB                       | 345.0             |  |
| Porsche                  | Porsche approved  |  |
| Saab                     | Saab approved     |  |
| Volvo                    | Volvo approved    |  |
| ZF                       | ZF TE-ML 02K      |  |

