



# XTS 5W20

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**Bardahl XTS 5w20** has been specially formulated for the lubrication of FORD EcoBoost petrol engines. It also applies to JAGUAR and LAND-ROVER petrol engines (excluding compressed V6 and V8).

## SPECIFICATIONS

This product offers the following performance level:

API	SP/RC
ILSAC	GF-6A
GM	Dexos 1TM Gen 2
FORD	WSS-M2C946-A
FIAT	9.55535-CR1
CHRYSLER	MS 6395

## PROPERTIES

- ✓ Avoids fuel over-consumption,
- ✓ Offers a stable viscosity and a high Viscosity Index,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold start easier,
- ✓ Provides an excellent resistance against « shearing »,
- ✓ Contains anti-corrosion, anti-wear and anti-foam additives.



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2  
T: (+32) (0) 69 59 03 60

[www.bardahl.fr](http://www.bardahl.fr)  
[www.bardahloils.com](http://www.bardahloils.com)



## TECHNICAL DATA

Density at à 15°C	Kg/l	0,848
Viscosity at -35°C	mPa.s	4160
Viscosity at 40°C	mm <sup>2</sup> /s	42,6
Viscosity at 100°C	mm <sup>2</sup> /s	7,85
Viscosity Index		157
Flash point COC, °C	°C	218
Pour point, °C	°C	-36
TBN Alcalinity	mgKOH/g	7,7
Sulphated Ash contents	%	0,78

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36291	12 X 1 L
36293	3 X 5 L
36298	20 L
36297	205 L

